?

?????????? (Switch, ????? ECS561052S) L2 ECS5610-52S Edge-Core





L2 48x10G SFP+4x40G+1xSlot

???????: ??? ????????
????:
???? ?? ???????:

????: 650700,00 ???.

??????? ?????? ?? ????? ??????

?????????????: Edge-Core

????????

ECS5610-52S
About this product
48 10Gigabit SFP+ ports supporting 10GbE or 1GbE
4 QSFP+ each supporting 40GbE or 4*10GbE
Switching Capability: 1.28Tbps
Forwarding Rate: 952Mpps

Product specification
Physical Configuration
Dimension (HxWxD) cm 4.3 x 44 x 47cm
Weight (kg) 7.3kg

Performance
Forwarding Rate 952Mpps
Switching Capacity 1.28Tbps

L2 Features
Flow Control Yes
IGMP Snooping v1 | v2 | v3
Jumbo Frame Yes
Link Aggregation IEEE 802.3ad with LACP (Dynamic) | Static Trunk
MVR Yes
Spanning Tree IEEE 802.1D (STP) | IEEE 802.1w (RSTP) | IEEE 802.1s (MSTP) | BPDU Filtering | Root Guard
Storm Control Broadcast | Multicast | Unknown Unicast
VLAN IEEE 802.1Q VLAN | Private VLAN | GVRP | Q-in-Q | MAC-Based VLAN | IP Subnet VLAN | Port-Based VLAN
VLAN Group 4K

L3 Features
Multicast Routing IGMP | PIM-DM | PIM-SM
Proxy ARP Yes
Unicast Routing RIP v1/v2
VRRP Yes

QoS Features

CoS IEEE 802.1p | IP Precedence | DSCP
DiffServ (RFC2474) Yes
H/W Queues 8
Rate Limiting Ingress | Egress

Security Features
HTTP and SSL (Secured Web) Yes
IEEE 802.1x Port-based | MAC-based | VLAN Assignment
RADIUS (RFC2138) Authentication | Accounting
SSH v1.5/v2 Yes
TACACS+ Authentication | Accounting | Authorization
Username/Password Authentication Local | Remote

Management Features
CLI Yes
DHCP for IP address assignment Yes
Firmware Download TFTP (RFC783)
Firmware Upgrade TFTP (RFC783)
IP Clustering Yes
LLDP Yes
Multiple configuration files Yes
RMON RMON I (1,2,3 & 9 groups)

IPv6 Features
IPv6 Multicast PIM-SM | PIM-DM

??????

??? ??????? ?? ???? ??????.