?

???????? ????????????? ??????? (UPS, ???) SC1000I APC



1000VA, 230V, 2U Rack/Tower, ???. ???. RBC33

???????: ??? ????????
????:

??????? ?????? ?? ????? ??????

?????????????: APC

????????

APC Smart-UPS SC 1000VA 230V - 2U Rackmount/Tower

Output

Output Power Capacity 600 Watts/ 1000 VA

Max Configurable Power 600 Watts/ 1000 VA

Nominal Output Voltage 230V

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal,57 - 63 Hz for 60 Hz nominal

Topology Line Interactive

Waveform Type Stepped approximation to a sinewave

Output Connections

(4) IEC 320 C13

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C14

Input voltage range for main operations 186 - 284V

Input voltage adjustable range for mains operation 175 - 297V

Communications & Management

Interface Port(s) DB-9 RS-232

Control panel LED status display with On Line : On Battery : Replace Battery and Overload indicators

Audible Alarm Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating 445 Joules

Filtering Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Data Line Protection RJ-45 Modem/Fax/DSL/10-100 Base-T protection

Physical

Maximum Height 89.00 mm

Maximum Width 432.00 mm

Maximum Depth 463.00 mm

Rack Height 2U

Net Weight 16.36 KG

Shipping Weight 19.56 KG

Shipping Height 254.00 mm

Shipping Width 610.00 mm

Shipping Depth 610.00 mm

Master Carton Units 1.00

Color Grey

Units per Pallet 10.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -5 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 45.00 dBA

Online Thermal Dissipation 180.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,GOST,VDE

Standard Warranty 2 years repair or replace

Environmental Compliance RoHS 7b Exemption,China RoHS,REACH: Contains No SVHCs

??????

??? ??????? ?? ???? ??????.