?

???????? ????????????? ??????? (UPS, ???) SC450RMI1U APC





450 VA, 1U Rack, RS-232, ???. ???. RBC18

???????: ??? ????????
????:

??????? ?????? ?? ????? ??????

??????????????: APC

????????

APC Smart-UPS SC 450VA 230V - 1U Rackmount/Tower

Output

Output Power Capacity 280 Watts/ 450 VA

Max Configurable Power 280 Watts/ 450 VA

Nominal Output Voltage 230V

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal,57 - 63 Hz for 60 Hz nominal

Topology Line Interactive

Waveform Type Stepped approximation to a sinewave

Output Connections

(4) IEC 320 C13

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C14

Input voltage range for main operations 160 - 286V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) DB-9 RS-232

Control panel LED status display with On Line : On Battery : Replace Battery and Overload indicators

Audible Alarm Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Emergency Power Off (EPO) Optional

Surge Protection and Filtering

Surge energy rating 320 Joules

Filtering Full time multi-pole noise filtering : 0.7% IEEE surge let-through : zero clamping response time : meets UL 1449

Data Line Protection RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines),RJ45 10/100 Base-T Ethernet protection

Physical

Maximum Height 44.00 mm

Maximum Width 432.00 mm

Maximum Depth 383.00 mm

Rack Height 1U

Net Weight 10.18 KG

Shipping Weight 11.73 KG

Shipping Height 164.00 mm

Shipping Width 476.00 mm

Shipping Depth 589.00 mm

Color Grey

Units per Pallet 24.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 38.00 dBA

Online Thermal Dissipation 38.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,GOST,VDE

Standard Warranty 2 years repair or replace

Environmental Compliance RoHS 7b Exemption,China RoHS

??????

??? ??????? ?? ???? ??????.