?

# APC Smart-UPS 700VA 230V Serial Black



???????: ??? ????????
**????:**

??????? ?????? ?? ????? ??????

?????????????: APC

????????

APC Smart-UPS 700VA 230V Serial Black

APC Smart-UPS, 450 Watts / 700 VA, Input 230V / Output 230V , Interface Port DB-9 RS-232, SmartSlot

Includes: CD with software, Smart UPS signalling RS-232 cable, User Manual

**Output**

Output Power Capacity 450 Watts / 700 VA

Max Configurable Power 450 Watts / 700 VA

Nominal Output Voltage 230V

Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage

Topology Line Interactive

Output Connections

(4) IEC 320 C13

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320-C14 inlet

Input voltage range for main operations 174 - 286V

Input voltage adjustable range for mains operation 168 - 302V

Communications & Management

Interface Port(s) DB-9 RS-232,SmartSlot

Available SmartSlot™ Interface Quantity 1

Control panel LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Optional

Surge Protection and Filtering

Surge energy rating 320 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 157.00 mm

Maximum Width 137.00 mm

Maximum Depth 358.00 mm

Net Weight 13.18 KG

Shipping Weight 14.55 KG

Shipping Height 279.00 mm

Shipping Width 273.00 mm

Shipping Depth 495.00 mm

Color Black

Units per Pallet 40.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 41.00 dBA

Online Thermal Dissipation 85.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,EN 50091-1,EN 50091-2,GOST,VDE

Standard Warranty 2 years repair or replace

**??????**

??? ??????? ?? ???? ??????.