?

???????? ????????????? ??????? (UPS, ???) SMX2200RMHV2U APC



2200VA, 1980 Watts, 2U, LCD, 230V, USB, SmartSlot

???????: ??? ????????
????:

??????? ?????? ?? ????? ??????

?????????????: APC

????????

APC Smart-UPS X 2200VA Rack/Tower LCD 200-240V

Output

Output Power Capacity 1980 Watts/ 2200 VA

Max Configurable Power 1980 Watts/ 2200 VA

Nominal Output Voltage 230V

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal,57 - 63 Hz for 60 Hz nominal

Other Output Voltages 208,220,240

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(8) IEC 320 C13

(1) IEC 320 C19

(2) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

IEC-320 C20

Schuko CEE 7 / EU1-16P

British BS1363A

Cord Length 1.83 meters

Input voltage range for main operations 141 - 255,160 - 280V

Other Input Voltages 208,220,240

Transfer Time 2-4 ms

ommunications & Management

Interface Port(s) SmartSlot,USB

Available SmartSlot™ Interface Quantity 1

Control panel LED status display with On Line : On Battery : Replace Battery and Overload indicators,Multi-function LCD status and control console

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Yes

Surge Protection and Filtering

Surge energy rating 645 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Data Line Protection --

Physical

Maximum Height 85.00 mm

Maximum Width 432.00 mm

Maximum Depth 667.00 mm

Rack Height 2U

Net Weight 37.32 KG

Shipping Weight 45.36 KG

Shipping Height 243.00 mm

Shipping Width 596.00 mm

Shipping Depth 869.00 mm

Color Black

Units per Pallet 8.00

# of Layers per Pallet 4

# of Units per Layer per Pallet 2

Pallet Weight 388.69 KG

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 55.00 dBA

Online Thermal Dissipation 150.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,CSA,EN 50091-1,EN 50091-2,FCC Part 15 Class A,GOST,IEC 60950,IRAM,UL 1778,VDE

Standard Warranty 3 years repair or replace (excluding battery) and 2 year for battery,optional on-site warranties available,optional extended warranties available

??????

??? ??????? ?? ???? ??????.