?

???????? ????????????? ??????? (UPS, ???) SUA5000RMI5U APC



5000 VA, 230V, Rack/Tower , ???. ???. RBC55

???????: ??? ????????
????:

??????? ?????? ?? ????? ??????

?????????????: APC

????????

APC Smart-UPS 5000VA 230V Rackmount/Tower

Output

Output Power Capacity 4000 Watts/ 5000 VA

Max Configurable Power 4000 Watts/ 5000 VA

Nominal Output Voltage 230V

Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage

Efficiency at Full Load 96.0%

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal

Other Output Voltages 220,240

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(8) IEC 320 C13

(2) IEC 320 C19

(4) IEC Jumpers

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 3 Hz (auto sensing)

Input Connections

Hard Wire 3-wire

Input voltage range for main operations 160 - 286V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) DB-9 RS-232,SmartSlot

Pre-Installed SmartSlot™ Cards AP9630

Control panel LED status display with On Line : On Battery : Replace Battery and Overload indicators

Audible Alarm Audible and visible alarms : configurable delays

Surge Protection and Filtering

Surge energy rating 480 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 222.00 mm

Maximum Width 483.00 mm

Maximum Depth 660.00 mm

Rack Height 5U

Net Weight 97.73 KG

Shipping Weight 106.82 KG

Shipping Height 635.00 mm

Shipping Width 610.00 mm

Shipping Depth 762.00 mm

Color Black

Units per Pallet 3.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -15 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-15000 meters

Audible noise at 1 meter from surface of unit 53.00 dBA

Online Thermal Dissipation 430.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,EN 50091-1,EN 50091-2,GOST,GS Mark,VDE

Standard Warranty 2 years repair or replace

Environmental Compliance RoHS 7b Exemption,China RoHS,REACH: Contains No SVHCs

??????

??? ??????? ?? ???? ??????.