?

???????? ????????????? ??????? (UPS, ???) SUM3000RMXLI2U APC



3000VA, 230V, Rack/Tower, ???. ???. RBC43

???????: ??? ????????
????:

??????? ?????? ?? ????? ??????

?????????????: APC

????????

APC Smart-UPS XL Modular 3000VA 230V Rackmount/Tower

Output

Output Power Capacity 2850 Watts/ 3000 VA

Max Configurable Power 2850 Watts/ 3000 VA

Nominal Output Voltage 230V

Output Voltage Note Configurable for 220 : 230 or 240 nominal output voltage

Efficiency at Full Load 95.0%

Output Voltage Distortion Less than 5% at full load

Output Frequency (sync to mains) 47 - 53 Hz for 50 Hz nominal,57 - 63 Hz for 60 Hz nominal

Topology Line Interactive

Waveform Type Sine wave

Output Connections

(7) IEC 320 C13

(1) IEC 320 C19

(2) IEC Jumpers

Bypass Internal Bypass (Automatic and Manual)

Input

Nominal Input Voltage 230V

Input Frequency 50/60 Hz +/- 5 Hz (auto sensing)

Input Connections

IEC-320 C20

Input voltage range for main operations 160 - 285V

Input voltage adjustable range for mains operation 151 - 302V

Communications & Management

Interface Port(s) DB-9 RS-232,RJ-45 10/100 Base-T,USB

Pre-Installed SmartSlot™ Cards AP9631

Control panel LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : Overload and Bypass Indicators

Audible Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO) Optional

Surge Protection and Filtering

Surge energy rating 490 Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height 86.00 mm

Maximum Width 432.00 mm

Maximum Depth 678.00 mm

Rack Height 2U

Net Weight 46.82 KG

Shipping Weight 56.82 KG

Shipping Height 250.00 mm

Shipping Width 596.00 mm

Shipping Depth 980.00 mm

Color Black

Units per Pallet 8.00

Environmental

Operating Environment 0 - 40 °C

Operating Relative Humidity 0 - 95%

Operating Elevation 0-3000 meters

Storage Temperature -20 - 45 °C

Storage Relative Humidity 0 - 95%

Storage Elevation 0-9000 meters

Audible noise at 1 meter from surface of unit 55.00 dBA

Online Thermal Dissipation 300.00 BTU/hr

Conformance

Regulatory Approvals C-tick,CE,EN 50091-2,EN 55022 Class A,EN 61000-3-2,GOST

Standard Warranty 2 years repair or replace

Environmental Compliance RoHS 7b Exemption,China RoHS,REACH: Contains No SVHCs

??????

??? ??????? ?? ???? ??????.